



. ?9/) ' 2 ' :'

%01+25-99 44)91+ =-1/0: / 4	90 65:-5: =-1/0: /	36= 8): -		
			31:8-9 415 4	*)8	31:8-9 415 4
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(

?%0- .6336=15/ .1/; 8-9)8- 56415)3 <); -9 .68 97 -+1.1+):1659 +65:)+: >6; 8 8-78-9-5:):1<-

49:8;):/549 ,58)588+): ; 9+

%. +4 /49+8:/4- /4:5 :. + ,/2:+8 68+99 . ' 4*2+ :. + ,/2:+8 9. ++:9 =/:.)' 8+ :5 +2/3/4' :+ *9:58:/54 58 ' (8' 9/54 +<+8 ; 9+ ' *' 3' -+* ,/2:+8 9. ++:

"5 +49; 8+)588+): ; 9+ 62')+ :. + 9355:.. 9/*+ 5, :. + ,/2:+8 9. ++: ' -' /49: :. + ,/2:8' :/54 62' :+ / + *5=49:8+' 3 ". + 85; -. 9/*+ 5, :. + ,/2:+8 9. ++: ;')+9 :. + 2/7; /* :5 (+ ,/2:+8+* / + ; 69:8+' 3

8/58 :5 :. + ,/89: ,/2:8' :/54 /: /9 8+)53 3+4*+* =. +8+ 6599/(2+ :5 68+ 8/49+ :. +)259+* ,/2:+8 =/:. ' 6685>/3' :+2? 2/:8+9 5, =' :+8 6+8 3 ' : :/3+9 :. + ,25= 8' :+ ; 8/4- 68+ 8/49/4-). +)1 ,58 2+' 1' -+ 8+ :/-.:+4 :5 +2/3/4' :+ /, 4+)+99' 8?

' 82954 8' 4-+ 5, & ,/2:+8 9. ++:9 3' ? (+ 9+8/2/9+* =/:. 9' :; 8' :+* 9+:' 3 58 .5: =' :+8 ". + 68+99+* ,/2:+8 6')1 . ' 9 :5 (+ 2559+4+* 92/-.:2? :5 +49; 8+ :. ' :. + 9+:' 3 . ' 9 +4:/8+2? 9+8/2/9+* :. + 9?9+3 /4' 2 68+99; 8+ 9. 5; 2* 542? (+ ' 662/+* :5 :. + ,/2:+8 6')1' -+ 54)+ :. + +4:/8+ ,/2:+8 . ' 9)552+* *5=4



Sterilisation with steam:

Steam quality:	Steam has to be free of foreign particles and impurities
Temperature:	max 134 ^o c (saturated steam)
Duration	20minutes

Sterilisation with hot water:

Water quality:	The water should be softened and be free of impurities
Temperature:	80-85 ^o c
Duration:	20 minutes

Sheet flushing

The Carlson range of XE filter sheets can be forward and back washed using softened water to extend the life and reduce the costs of filtration. This is, however, very much dependent upon the application and filtration conditions.

Regeneration procedure:

Cold rinsing:	in direction of filtration for approximately 5-10 minutes
Temperature	15-20 ^o c
Hot rinsing;	forward or reverse direction of filtration for approximately 10 minutes
Temperature	60-80 ^o c

Safety and disposal

Used under the correct conditions the Carlson range of XE filter sheets have no known negative effects and can be disposed of through normal route, observing local and official regulations. Consult MSDS for further information.

Storage

Store in a place which is dry, cool and free from strong odours.

Forms of supply

XE range of filter sheets are available in all customary sizes, hygienically shrink-wrapped and packed in cardboard boxes. Special formats are available on request.

Remarks

All Carlson Filtration Ltd filter sheets are manufactured in accordance with BfR recommendation XXXV1/1 (regulations regarding paper and board designed for contact with foodstuffs) and EC Regulation No 1935/2004 (materials and articles intended to come into contact with food).

All our products are made according to the rules of Quality Management System EN ISO 9001:2008

We provide information and advice to the best of our knowledge. This information cannot be binding in every case on account of the variety of applications, work methods and operating conditions. We, therefore, cannot assume liability for improper use.



Van Borselen b.v.

Argonstraat 66
 2718SN Zoetermeer

Tel.: +31 (0)79 34 12 314

Fax.: +31 (0)79 34 12 892

Email: info@vanborselen.nl

Web: www.vanborselen.nl